



### Properties

- Free-flowing powder
- Starts the chemical reaction of Silikal MMA resins

### Area of application

- Second component of Silikal MMA resins to start the chemical reaction

### Advice on application

- **⚠ Never expose SILIKAL® BPO to direct heat or store it in the sun!**
- Stir in SILIKAL® BPO until it is fully dissolved (approx. 1 minute or approx. 2 minutes for temperatures below +5 °C) and then use the mixture immediately.
- Only use plastic scoops to remove from larger containers, never metal ones.
- Opened containers must be closed after use.
- The hardener dosage is based on the "Hardener dosages" tables in the data sheets of the individual resins.



#### Other applicable documents

Corresponding Silikal resin	Data sheet
General notes	Technical documentation MMA
Safety data sheets	All used Silikal products

The information in this data sheet replaces all previous information about the product and its application. The application instructions as well as the technical data of the product are only guidelines. The buyer is responsible for the application and claims of third parties.

#### Silikal Product Information

Data sheet SILIKAL® BPO  
Page 1 of 1  
Issue MMA 7.02A – February 2023



#### Silikal GmbH

Ostring 23 · 63533 Mainhausen · Germany  
Phone: +49 (0) 61 82 / 92 35-0  
mail@silikal.de · www.silikal.de